



HLX Range

Diesel engine lubricants

Description

Castrol HLX is a Super High Performance Diesel (SHPD) lubricant, specially formulated to meet the latest performance requirements of marine monograde lubricant specifications. This allows extended drain periods to effectively compete with performance normally associated with synthetic oils. HLX is available in both SAE 30 and 40 viscosity grades.

Application

HLX, positioned at the top of the Castrol range of mineral based diesel engine lubricants, is formulated for use in very highly rated high speed marine and power generation diesel engines that use distillate fuel with sulphur from zero up to 1% and require extreme performance. It is particularly suitable for high power density applications such as fast ferries.

Advantages

HLX uses premium additive technology blended in high quality, high viscosity index base oils. It provides high detergency and excellent thermal and oxidative stability required to lubricate today's most severe diesel engine applications.

In summary, HLX can enable:

- Extended oil drain intervals compared to other API CF oils.
- Excellent high temperature performance.
- High resistance to bore polishing.

Product Performance Claims

HLX 30 and HLX 40 are approved by all the major OEM's, including approval as a `Type 2` MTU monograde lubricant, that allows oil drain intervals to be doubled compared to standard marine oils.

HLX additive technology exceeds API CF and ACEA E3 - tested to MB 228.2, MAN M3275 and Volvo VDS-2.

Typical Characteristics

Name	Method	Units	HLX 30	HLX 40
SAE Grade			30	40
Density @ 15°C	ASTM D4052	g/ml	0.9	0.9
Viscosity @ 100°C	ASTM D445	mm ² /s	11.5	14.0
Base Number	ASTM D2896	mg KOH/g	12	12
Closed Flash Point	ASTM D93	°C	225	228
Pour Point	ASTM D97	°C	<-15	<-15

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

HLX Range

09 Oct 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine